

# ESP8266 AT Release v2.2.0.0

---

Documentation for v2.2.0.0 is available at [https://docs.espressif.com/projects/esp-at/en/release-v2.2.0.0\\_esp8266/](https://docs.espressif.com/projects/esp-at/en/release-v2.2.0.0_esp8266/)

ESP-AT v2.2.0.0 is a major update for ESP-AT v2.1.0.0.

## Changelog

---

This is the list of changes since release v2.1.0.0:

### Breaking Changes

- **ESP8266\_RTOS\_SDK** version updated to release v3.4 (967752e)
- Compiler upgraded from v5.2.0 to v8.4.0
- AT+CIPDOMAIN: Double quotation marks are added to the string parameters in the response
- Added WROOM-02-N, WROOM-S2, WROOM\_5V2L, ESP8266\_1MB module support
- AT commands supports IPv6 network now
- ESP8266 SPI AT does not support any more (ESP32-C3 recommended)

### Known Issue

- AT+CWJAP: **listen\_interval** parameter is wrong in the query command response

## 1. Feature

### 1.1 Wi-Fi

- AT+CWRECONNCFG: Support to configure Wi-Fi reconnect interval and maximum retry times
- AT+CWLAPOPT: Support to filter the scanned result by rssi and authmode
- AT+CWJAP: Limit the range of listen interval to [1, 100]
- AT+WPS: Support authmode floor configuration
- AT+CWSMARTSTART: Support authmode floor configuration
- AT+CWLAP: Support the information of 802.11 b/g/n in the response
- AT+CWJAP: Support to configure timeout and pmf, and connect the last recorded AP
- AT+CWSTATE: New Command to query Wi-Fi state

### 1.2 TCP/IP

- AT+SYSMSG: Extended BIT2 parameter for passthrough mode
- AT+CIUPDATE: Support to upgrade custom partitions and asynchronous OTA
- AT+PING: Added an error message **TIMEOUT** for incorrect DNS
- Modified tcp mss and wnd to improve compatibility

- Modified tcp mss, from 1460 to 1440
- Modified tcp wnd, from 5840 to 5760
- Modified tcp snd buf, from 2920 to 2880
- Replaced wolfSSL with mbedTLS in SSL connection
- Disabled setting AT+CIPSSLCCN, AT+CIPSSLCSNI, AT+CIPSSLCALPN, AT+CIPSSLCPSK if the link is already connected
- AT+CIPSERVER: Added close\_all\_clients parameter to close all connections which connected the server created by AT+CIPSERVER
- The following AT commands supports IPv6 since v2.2.0.0
  - AT+CIPV6
  - AT+CIPSTATUS
  - AT+CIPDOMAIN
  - AT+CIPSTART
  - AT+CIPSTARTEX
  - AT+CIPSERVER
  - AT+SAVETRANSLINK
  - AT+PING
  - AT+CIPDNS
  - AT+CIPSTA
  - AT+CIPAP
  - AT+CIFSR

### 1.3 Application Layer

- AT+CIPSNTPCFG: Support to configure half timezone offset
- AT+MQTTCONNCFG, AT+MQTTPUB, AT+MQTTPUBRAW, AT+MQTTPUB, AT+MQTTUNSUB command supports 128 bytes topic
- AT+WEBSEVER: New command to support Wi-Fi provisioning via SoftAP and Captive Portal
- AT+HTTPCLIENT: Support chunked data
- AT+HTTPCPOST: New command to support long data post

### 1.4 System

- AT+CMD: New command to query the supported AT commands list
- AT+USERAM: New command to alloc ram for host mcu to use it
- AT+SYSREG: New command to read and write registers
- AT+SYSRAM: Support to query the minimum heap size
- AT+GMR: Added chip platform information in the response

## 2. Bugfix

### 2.1 Wi-Fi

- Fixed AT+CWLAP issues

- Fixed AT+CWLAP returned ERROR when total active scan time is more than 15 seconds
- Fixed AT+CWLAP did not return ap in the response sometimes
- Fixed AT+CWLAP blocked more the 10 seconds sometimes
- Fixed AT+CWLAP rssi filter parameter could not work sometimes
- Fixed AT+CWLAP could not scan valid ap by ssid and bssid
- Fixed the issue that `AT+CWMODE=1, 1` could not auto-connect to AP when Wi-Fi mode switched from `WIFI_MODE_NULL`
- Fixed the issue that AT+CWJAP may return wrong error number
- Fixed AT+WPS failed on multiple ap credentials case
- Fixed AT+CIPSTA/AT+CIPAP could set wrong IP address due to the lack of rigorous address check

## 2.2 TCP/IP

- Fixed wrong state of AT+CIPSTATUS command
- Fixed data error in passthrough mode with 2Mbps baud rate
- Fixed AT+CIPRECONNINTV did not work immediately
- Fixed that the received data was incomplete if the data was too large in softAP mode
- Fixed AT+CIPSENDEX data was truncated in advance
- Fixed AT+CIPSEND returned ERROR sometimes
- Fixed crash when link id < 0
- Fixed AT+CIPMUX=0 set error when all connections closed
- Fixed SSL link may not disconnect when IP address changed
- Fixed potential blocking when hardware flow control enabled
- Fixed an issue of mistakenly printing "CLOSED" or "+LINK\_CONN"
- Fixed tcp server could not work again if the link closed and opened repeatedly
- Fixed AT+SAVETRANSLINK could not work sometimes
- Fixed AT+CIPSERVER could set mode to 2
- Fixed AT+CIPSTART SSL connect failed if disabled ALPN by AT+CIPSSLCALPN=1,0
- Fixed tcp send data lost in passthrough mode

## 2.3 Application Layer

- Fixed AT+MQTTCONN returned ERROR when checking common name
- Fixed AT+MQTTUSERCFG? crash after MQTT connected
- Fixed AT+CIPSSLCALPN query command caused to reboot due to memory coverage
- Fixed AT+MQTTCONN may cause wdt reset when input some special hostname
- Fixed the issue that AT+HTTPCLIENT url failed to be omitted

## 2.4 System

- Fixed AT+GSLP did not return OK sometimes
- Fixed AT+GSLP may return ERROR when setting a long deep sleep time
- Fixed wrong uart pins disabled before deep-sleep
- Fixed AT+SLEEPWKCFG did not check GPIO configuration issue
- Fixed the crash when sending command with one redundant character "" before "\r\n"
- Fixed AT+SLEEP=2 returned OK in softap mode
- Fixed silence firmware crash sometimes

- Fixed build fail when disable customized partition
- Fixed sdio read data error when length bigger than sdio list

### 3. Optimization

- Added build.py script to simplify the compilation process and supported windows OS compilation
- Refactored application directory
- Removed deprecated GNU make
- Supported spi & sdio example cmake
- Removed at\_http\_webserver example